

INFRARED DIODE LASER AT 940nm

RN-H-940/2000~4500mW

产品描述

It features ultra compact design, long lifetime, cost-effectiveness and easy operation. They are used in measurement, communication, spectrum Analysis, etc.

产品参数

| RN-H-940/2000~4500mW | | |
|-------------------------------------|--|-----------|
| Central wavelength (nm) | 940±5 | |
| Operating mode | CW | |
| Output power (mW) | >2000, 2500, ... , 4500 | |
| Power stability (rms, over 4 hours) | <1%, <2%, <3% (<0.5%, optional) | |
| Transverse mode | Multimode | |
| Beam diameter at the aperture (mm) | ~5×8 | |
| Beam divergence, full angle (mrad) | <3. 0 | |
| Warm-up time (minutes) | <5 | |
| Beam height from base plate (mm) | 29 | |
| Operating temperature (°C) | 10~35 | |
| Power supply (100-240VAC) | PSU-H-LED | PSU-H-FDA |
| TTL / Analog modulation | TTL or Analog with 1Hz-1kHz 1kHz-10kHz, 10kHz-30kHz, 30kHz-100kHz optional | |
| Expected lifetime (hours) | 10000 | |
| Warranty | 1 year | |

北京市昌平区

国家信息产业基地立业路13号2011

sales@ranbond.com